



at



DAEWOO

Standard Equipment

- * 128.2HP rated engine power
- * 22500kg operating machine weight
- * Heavy duty lifting, consisting of new counterweight, toolbox weights and chassis weights
- * Complete with a mono or 2 piece boom
- * Twin tyres
- * Travel under OHLE
- * Full CE marking



- * Emergency towing points, complete with towbar
- * Hammer/rotate and bucket services
- * Trailer lighting cables at both ends
- * Automatic rail lighting on chassis
- * Extra work lighting on cab, boom and tail
- * Extra horn
- * Network Rail approval to RIS-1530-PLT
- * Duty charts available on request

- * Towing capacity of 20T
- * 650mm rail wheels
- * 150mm rail axles, one of which is an oscillating type with hydraulic locking for lifting purposes
- * Trailer service braking on travel levers
- * Trailer coupling front and rear
- * Trailer breakaway alarm system
- * Philmor trailer personnel cage emergency system
- * Fully adjustable rail gear
- * Trailer park braking



AT



Standard Equipment

- * Trailer lighting electric socket
- * Trailer brake system powered from main drive
- * RCI PC graphic system c/w slew and height limitation
- * Emergency hydraulic recovery system for boom, dipper and slew recovery
- * Machine lifting points



Above: Emergency towbar



Above: Optional twin cab

Optional Equipment

- * LUL spec and approval including:
 - Deadman system
 - 3 or 4 emergency stops
 - Counterweight marker lights
 - White hand rails and steps
 - Extra lights on dippe
 - Fire extinguisher
 - Chassis slew stops

Optional Equipment

- * Shortened dipper to 1.7m for increased lifting performance
- * Twin cab option available
- * Vandal guards
- * Work under OHLE
- * Offset boom
- * Fire extinguisher
- * Black and white or colour CCTV
- * Customer specific quick hitch supplied and/or fitted



Above: Machine with boom attachments